

## Product Data Sheet

### migra TFT 55"/65"/75" – IP54/65

Diagonal	55" / 139 cm	65" / 164 cm	75" / 190 cm
----------	--------------	--------------	--------------

#### Display

Active screen dimensions (h x v)	1209 x 680 mm	1428 x 803 mm	1650 x 928 mm
Resolution (pixel)	3840 x 2160	3840 x 2160	3840 x 2160
Viewing angle (typical)	178° H, 178° V	178° H, 178° V	178° H, 178° V
Brightness (typical)	500 cd/m <sup>2</sup> (panel typ.)	500 cd/m <sup>2</sup> (panel typ.)	500 cd/m <sup>2</sup> (panel typ.)
Colour performance	16.7 mio colours simultaneously (full colour)	16.7 mio colours simultaneously (full colour)	16.7 mio colours simultaneously (full colour)
Backlight system	LED	LED	LED
Protective glass	anti-glare	anti-glare	anti-glare
Mounting	VESA 600 x 400mm (4 x M6)	VESA 600 x 400mm (4 x M6)	VESA 800 x 800mm (8 x M8)

#### Environmental conditions

IP protection	IP 65 all around; or optional IP 54 on the front, Rest IP40
Temperature (operating)	0°C to + 45°C, optional -20°C to + 50°C
Temperature (storage)	-20°C to +60°C
Humidity	10% to 90% (non condensing)

#### Power

Power consumption	115V to 230V, 50Hz to 60Hz, optional 24 or 48VDC
-------------------	--

#### Dimensions

B x H x T	ca. 1300 x 770 x 100 mm	ca. 1525 x 900 x 100 mm	ca. 1746 x 1025 x 217 mm
Weight (+/-10%)	ca. 56 Kg	ca. 70 Kg	ca. 100 Kg

#### Colour

Standard colour cabinet	RAL 9005 (black), powder coated
Customized colour	On request

## Display with IPC (integrated Industrial PC)

Display supplied with integrated industrial PC

IPC	
Processor	Intel® Celeron® or Intel® Core™ i5, etc.
HDD	min. 60 GB SSD up to 256 GB
RAM	min. 4GB up to 16GB
Network adapter Ethernet	1 x 1000
USB 2.0	2x
RS232	(optional)
HDMI	(optional)
Audio Lineout	(optional)
Software installed	Optional: - WIN 10 or WIN 11 prof. 32-Bit - WIN 10 or WIN 11 prof. 64-Bit - WIN 10 or WIN 11 IoT Enterprise 2019 LTSC 64-Bit - Windows Embedded®

## Display with Monitor-Electronics

Monitor for connection to external signal sources

Connectors	
Input	HDMI, DP, DVI or VGA optional additional connections on request

**Options**  
 VSG-pane, Wall mounting kits, Ceiling mounting kits, IR remote control (only monitor), Stainless steel front, Loudspeaker



Example